



Product Installation Steps

1

Fasten the connecting screws

Please fix the main rod as shown in the picture first

3 connecting rods

8 forks

Fasten the connecting screws

Straight pipe

3 forks

Tips: When installing, make sure the wire hook is facing upwards as shown in the picture!

1. Pass the bottom lamp holder with all the teeth through the trident and put on the water pipe, pass it through the cover under the lamp drum and tighten the nut.
2. Connect the male and female wires. Use 3 threaded tubes to connect the lamp drum and the cover and tighten the flat head nut.

Expansion screws

Hanging board

Self-tapping screws (4 screws to fix the hanging plate)

Terminal Blocks

Bucket ring

Locking rod ring (fixed half disc)

screw

To prevent tilting, please hang the glass pendants on the lamp stand symmetrically from the bottom.

2

Expansion screws

Hanging board

Self-tapping screws (4 screws to fix the hanging plate)

Terminal Blocks

Bucket ring

Locking rod ring (fixed half disc)

screw

- 1 Drill holes in the ceiling first according to the hole spacing of the hanging board
- 2 Insert the plastic expansion screw
- 3 Drive the self-tapping screws through the holes in the hanging board and into the plastic expansion screws to fix the hanging board.
- 4 Connect the wires
- 5 Connect the bucket ring to the boom and hang it on the hook, push the semicircle up and secure it with the ring.

